

GTA015



Regulating damper in aluminum with blades pitch 150 mm with opposed movement.

MATERIAL AND FINISH


A Frame in natural aluminum (series 5005), 4 welded pieces, flange 40 mm, thickness 1.5 mm.

B Extruded aluminum blades (series 6060) with wing profile, opposed movement.

C Pins in galvanized steel Ø12 mm secured to the blades with bolts.

D NYLON bushes.

E Aluminum side plates



VERSIONS

- GT015 T Gas tightness Class 2 B EN1751 + 10% (PRICES UPON REQUEST)
- Painting
- ATEX II 2 GD + 33 €

ACCESSORIES

Manual commands see page 273.
Electric actuators see page 274.

DIMENSIONS AND PRICES

Blades no.	Z [mm]	H [mm]	W [mm]								
			200	300	400	500	600	700	800	900	1000
			€	€	€	€	€	€	€	€	€
2	80	310									
3	80	460									
4	380	610									
5	380	760									
6	380	910									
7	380	1060									
8	680	1210									
9	680	1360									
10	680	1510									
11	680	1660									
12	980	1810									
13	980	1960									
14	980	2110									
15	980	2260									
16	1280	2410									

NB: For the prices of the intermediate sizes, consider the next size on the table.

Ex.: 250 x 310 mm = 300 x 310 mm

For basic sizes > 2000 mm, construction in double dependent section:

just one command that moves the two sections at the same time.

Composition of price:

2600 x 760 mm = 2* 1300 x 760 mm

Torque min; 8 Nm/m²

* See tech data sheet

