

**MATERIAL AND FINISH**

Traction device in hardened galvanised steel.

**APPLICATION**

- Suitable for any diameter of flexible ducts.

**PRICES**

Model	Ø min	Ø max	NEM
NEM	[mm]	[mm]	€
110	60	110	•
135	60	135	•
170	60	170	
215	60	215	
270	60	270	
325	60	325	
380	60	380	
525	60	525	
660	60	660	

- Products in stock



Adhesive tapes

**MN / NV****MN****MATERIAL AND FINISH**

Aluminum laminate tape and synthetic rubber-based adhesive.

**APPLICATIONS**

Used as joint covering or reinforcement binding to ensure air, water and steam tightness.

**TECHNICAL SPECIFICATIONS**

- Operating temperature -5° C +70° C

**NV****MATERIAL AND FINISH**

Cotton cloth tap impregnated with polyethylene and natural rubber-based adhesive.

**APPLICATIONS**

Particularly suitable for sealing air and air conditioner ducting.

**TECHNICAL SPECIFICATIONS**

- Operating temperature -5° C +70° C
- High mechanical resistance
- Excellent adhesiveness rating
- Heat and atmospheric agent stability,
- Air, water and steam tightness

**PRICES**

Model	Height	MN
	[mm]	€
MN50	50	•
MN75	75	•

- Products in stock

Model	Height	NV
	[mm]	€
NV50	50	•

- Products in stock